



JL-12

Tube bending lubricant

FEATURES

- Easy to clean
- Gel formulation for no drip application - lowers amount of lubricant used/wasted
- Eliminates spilled/sprayed fluids
- Weldable with low smoke
- No build-up or residue
- Clean alternative to liquid lubricants
- Petroleum and pigment free

APPLICATIONS

- Great formula for bending stainless steel pipes and other materials Please call for consultation on specific applications

DIRECTIONS

Metal Mates JL-12 is supplied ready to use. Do not dilute.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

Appearance / Physical State	gel
Odor	mild odor
pH Value	7.5-8.5 at 10%
Specific Gravity	0.95
Flash Point	>200F (>93C)
Boiling Point / Range	212F (100C)
Vapor Pressure	<1
Prop 65 Warning	Yes
Dilution Ratio	Metal Mates JL-112 is supplied ready to use do not dilute

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM4002	5 gal	pail	1	opaque
MM4003	55 gal	drum	1	opaque
MM4006	330 gal	tote	1	opaque



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved