

Accu-Lube® Power Stamp II

Light Viscosity MQL

FEATURES

- Superior, heavy-duty minimum quantity lubricant with non-chlorinated extreme pressure and anti-wear additives.
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating

APPLICATIONS

- Operations that generate a lot of heat
- Stamping
- Machining aluminum and titanium
- For ferrous & nonferrous metals, aluminum and titanium
- Carbide die stamping

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose in accordance with all applicable regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Purple
Odor	Mild
Boiling Point / Range	>399.2°F (>204°C)
VOC Content	15.89 g/L per US State & Federal Consumer Product Regulations
Flash Point	400°F (204°C)
Pour Point	-38°F (-39°C)
Viscosity	15 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LBSTII01	1 gal	jug	4	34 lbs
LBSTII55	55 gal	drum	1	470 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved