

Accu-Lube® LB-4600

Light Viscosity MQL

FEATURES

- Economical, light-duty minimum quantity lubricant
- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

APPLICATIONS

- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose in accordance with all applicable regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Purple
Odor	Mild
Boiling Point / Range	>302°F (>150°C)
Flash Point	335°F (168°C)
Pour Point	40°F (4°C)
Specific Gravity	0.86
VOC Content	5.91 g/l
Viscosity	7.3 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB4600	1 gal	jug	4	34 lbs
LB4655	55 gal	drum	1	454 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved