

# Accu-Lube® Synthetic II

## General Purpose MQL

### FEATURES

- Economical, water-based minimum quantity lubricant with non-chlorinated extreme pressure and boundary additives for moderate-duty near-dry stamping and machining.

### APPLICATIONS

- Stamping
- General machining, sawing and cutting
- Economical
- Water-based, synthetic lubricant
- Provides excellent corrosion protection
- Boron free with superior lubricity
- For ferrous & nonferrous metals and aluminum
- Clean before heat treating with rinse water

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes and clothing. Wear protective gloves/protective clothing/eye protection/face protection.

### STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

### DISPOSAL

Dispose of in accordance with local regulations.



### PHYSICAL PROPERTIES

<b>Appearance / Physical State</b>	Liquid
<b>Odor</b>	Mild
<b>Color</b>	Light amber
<b>pH Value</b>	9
<b>Boiling Point / Range</b>	212.0°F (100.0°C)
<b>Flash Point</b>	>212.0°F (>100.0°C)
<b>Water Solubility</b>	Soluble.
<b>Specific Gravity</b>	1.05
<b>Pour Point</b>	35°F (2°C)
<b>Viscosity</b>	2 cSt @ 40°C

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LBSY201	1 gal	bottle	4	36 lbs
LBSY255	55 gal	drum	1	499 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved